

# **Grout Protector**

Easy to apply quick drying spray-on formula / Long lasting protection against water, dirt, grease, mould and limescale

Suitable for both wall and floor grout and natural stone borders / Overspray dries invisible

#### **DESCRIPTION**

Forms a colourless barrier and helps to protect porous wall and floor grout joints from penetration by water, dirt, oil, grease and limescale, making treated surfaces easier to keep clean. Ideal for use in wet rooms and shower enclosures. Used as a 'top up coat' this product is an easy way to further protect natural stone and all other types of masonry surface. Overspray on most surfaces will completely dissipate and not leave any hard to remove residue. When sealing a porous stone it is advisable to use a suitable liquid impregnator such as ROCATEX Natural Finish Sealer or ROCATEX Colour Intensifier before finishing with ROCATEX Grout Protector to achieve the best result.

#### **DIRECTIONS**

Areas to be treated must be cleaned. Older contaminated and dirty grouting should be cleaned with ROCATEX Mould Remover and then rinsed thoroughly. Newly grouted surfaces should be left to cure for 20-30 minutes and should be clean and free from dust before application. Always test the product on an inconspicuous area for suitability before general application.

Shake can well. Spray 15-20 cm from the surface and spray in a sweeping motion. Touch dry within 5 minutes. A 2-3 hour curing time is recommended upon completion before allowing traffic.

For wet areas including shower enclosures and wet rooms allow the sealer to cure for a minimum of 24 hours before use. Test area after application with a little water, if the water is absorbed, a second or even third coat may be required to obtain maximum performance.

Use only in open or well ventilated areas. Open windows and if possible use fans to circulate air. It is recommended that a suitable respiratory mask be worn at all times.

Overspray on highly polished porcelain or stone and highly glazed surfaces may in some cases leave a slight residue, in which case wipe up any excess within 5 minutes.

Stubborn residues left on the surface can be removed with the application of more ROCATEX Grout Protector which should then be buffed off immediately.

Do not spray on to acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Shake can well before use. Use only as directed.

## **COVERAGE: M<sup>2</sup> PER COAT**

On surfaces: Per 600ml, 5-25m depending upon the porosity and number of coats required. On grout joints: Per 600ml, 600 linear metres depending upon the width of the grout joint and number of coats required.

#### STORAGE INFORMATION

Store in a cool, dry, frost free environment.

### **HEALTH, SAFETY & ENVIRONMENTAL**

Contains: PROPAN-2-OL, HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, N-BUTYLACETATE. ISOPROPYL ACETATE.

Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.contents, container to a hazardous or special waste collection.







**DANGER**