# ROCATEX TECHNICAL DATA SHEET / Resin Residue Remover / 21 August 2023



# **Resin Residue Remover**

# **PAVING / PORCELAIN / STONE**

Softens hard to remove epoxy, acrylic and silicone residues left by cement free brush in jointing compounds making removal easier / Exterior Use

### **DESCRIPTION**

A low odour non caustic treatment that softens hard to remove epoxy, acrylic and silicone residues left by cement free brush in jointing compounds making removal from the surface of natural stone and porcelain paving much easier.

## **DIRECTIONS**

### SHAKE WELL BEFORE USE.

Always test on a inconspicuous area prior to general use.

# Preparation

Ensure that the surface to be treated is completely clean and dry. If necessary, first wash surfaces with ROCATEX Tile & Stone Renovator. Rinse well with water and leave to dry.

# Removing Residues

Apply generously by dabbing or rolling onto the surface. Work in manageable areas at a time and do not brush out. Leave for up to 30 minutes. If drying should occur within 30 minutes apply a little more solution to keep it wet. Use a stiff short haired brush or nylon scrubbing pad to remove the softened residues from the surface. Add a little water and scrub again. Extract the released residues using a sponge or wet vac and rinse with water. Repeat the process if unwanted material remains.

Use ROCATEX Tile & Stone Renovator dilute 1: 5 in warm water. Apply with a light pressure sprayer or watering can. Agitate the surface using a deck brush or nylon scrubbing pad. Rinse by hosing off thoroughly with clean water. Do not use when surface temperatures are under 5°C or over 25°C.

### **COVERAGE: (PER LITRE)**

Light stripping 8-10m<sup>2</sup> Deep stripping 5m<sup>2</sup>

## STORAGE INFORMATION

Store in a cool, dry, frost free environment.

Shelf life up to 2 years for un-opened containers.

Once opened use within 6 months of purchase for optimum results.

### **OTHER**

Do not apply during rain, frost, or when surface and air temp is under 5°C or over 30°C. Use gloves and protective goggles if there is a risk of direct contact or splashing. Empty containers are recyclable. Clean application tools and brushes with water after use. Once cleaned: Protect porous stone and porcelain with ROCATEX Paving & Stone Patio Sealer or ROCATEX Pre Grout Porcelain Tile Protector.

# ROCATEX

Rocatex Ltd Camwal Park Camwal Road Harrogate, HG1 4PT T: +44 (0)1423 882 990 F: +44 (0)1423 299 040 E: info@rocatex.com www.rocatex.com

# ROCATEX TECHNICAL DATA SHEET / Resin Residue Remover / 21 August 2023

# **HEALTH, SAFETY & ENVIRONMENTAL**

CONTAINS: benzyl alcohol. Harmful if swallowed or if inhaled. Causes serious eye irritation. Keep out of reach of children.

IF SWALLOWED: Immediately call a POISON CENTRE, a doctor. Do not breathe vapours, spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents, container to a hazardous or special waste collection point. If skin irritation or rash occurs: Get medical advice/attention.

